



Manufacturer's Certification Statement, Revision 15,

Issued January 01, 2016 page 1 of 3

Manufacturer's Certification Statement

To: All Viwinco Building Professional Customers and Homeowner Customers:

This letter is to verify that the Viwinco exterior window products as listed on the following pages are Eligible Building Envelope Components.

- a) Products shipped between January 1, 2016 and December 31, 2016, meet or exceed prescriptive criteria in all climate zones as established by the IECC for energy tax credit consideration for exterior window products.
- b) Products shipped as of the date indicated on the matrix on the following pages meet or exceed the energy performance criteria as set forth. All qualifying windows must meet ENERGY STAR; the window limit incentive is \$200.00.

This letter is provided as a verification in lieu of the appropriate labeling for those products ordered and received in the early stages of our manufacturing changes, prior to formal certification and formal labeling approval from the labs that review and certify Viwinco products.

The expanded time line of the product alterations made by Viwinco to meet the Energy Tax Criteria (initially to change glass packages in style offerings and then to switch nearly all products to the Intercept ULTRA spacer) not only illustrates our course of actions, but also indicates when ARRA criteria-compliant products were being shipped. Please note that as of April 17, 2009, ALL formal, National Fenestration Rating Council (NFRC) third party-approved certifications and labeling were in hand and in use.

Under penalties of perjury, I declare that I have examined this certification statement, and to the best of my knowledge and belief, the facts are true, correct, and complete.

A handwritten signature in black ink, appearing to read 'David J. Barnes', is written over a light blue horizontal line.

David J. Barnes

P.O. Box 499 | 851 Hemlock Road
Morgantown, PA 19540-0499

610.286.8884 | F. 610.286.0600
[Visit us at www.Viwinco.com](http://www.Viwinco.com)



STANDARD ZONE

| Product Line | Date Met. 2016 Energy Star Criteria | Style Details | Size Limitation | Glass Package Details of product supplied and shipped as of date listed: |
|---|-------------------------------------|---|-----------------|--|
| REPLACEMENT | | | | |
| Edgemont® | January 1, 2016 | Double-hung all styles | 36" x 72" max | ¾" IG unit with single strength Solarban 70 low-e glass, Intercept ULTRA spacer and argon gas fill |
| | January 1, 2016 | Double-hung all styles | 48" x 72" max | ¾" IG unit with single strength Solarban 70 low-e glass, Intercept ULTRA spacer and argon gas fill and composite reinforcement |
| | January 1, 2016 | Slider all styles | none | ¾" IG unit with single strength Solarban 70 low-e glass, Intercept ULTRA spacer and argon gas fill (3 Lite sliders are made with double strength glass) |
| | January 1, 2016 | Picture with grids only | none | ¾" IG unit with double strength Solarban 70 low-e glass, Intercept ULTRA spacer and argon gas fill |
| Cambridge™ | January 1, 2016 | Double-hung & Single-hung with and without grids | 48" x 72" max | 15/16" IG unit with double strength Solarban 70 low-e glass, Intercept ULTRA spacer and argon gas fill |
| | January 1, 2016 | Double-hung & Single-hung with and without grids | 48" x 72" max | ¾" IG unit with single strength Solarban 70 low-e glass, Intercept spacer and argon gas fill |
| | January 1, 2016 | Slider styles all styles | none | 15/16" IG unit with Double strength Solarban 70 low-e glass, Intercept ULTRA spacer and argon gas fill |
| | January 1, 2016 | *Picture all styles | none | 15/16" IG unit with Double strength Solarban 70 low-e glass, Intercept ULTRA spacer and argon gas fill *Non-grid picture windows made with triple strength glass as of September 9, 2009 |
| OceanView® | January 1, 2016 | Double-hung & single-hung with and without grids | 48" x 72" max | 15/16" IG unit with laminated double strength Solarban 70 low-e glass, Intercept ULTRA spacer and argon gas fill |
| | January 1, 2016 | Casement, Awning, *Picture with and without grids | none | 15/16" IG unit with laminated double strength Solarban 70 low-e glass, Intercept ULTRA spacer and argon gas fill *Non-grid picture windows made with triple strength glass as of September 9, 2009 |
| | January 1, 2016 | Double-hung and single-hung with and without grid | 48" x 72" max | 15/16" IG unit with laminated double strength Solarban 70 low-e glass, Intercept Spacer and argon gas fill |
| | January 1, 2016 | Casement, Awning, *Picture with and without grids | none | 15/16" IG unit with laminated double strength Solarban 70 low-e glass, Intercept Spacer and argon gas fill *Non-grid picture windows made with triple strength glass as of September 9, 2009 |
| | January 1, 2016 | Slider all styles | none | 15/16" IG unit with laminated double strength Solarban 70 low-e glass, Intercept Spacer and argon gas fill |
| OceanView® Geometric Styles | January 1, 2016 | Geometric windows with grids only | none | 15/16" IG unit with laminated double strength Solarban 70 low-e glass, Super spacer and argon gas fill |
| Viwinco Complementary Styles | January 1, 2016 | Casement & Awning | none | 15/16" IG unit with Double strength Solarban 70 low-e glass, Intercept ULTRA spacer and argon gas fill |
| | January 1, 2016 | Casement & Awning | none | 15/16" IG unit with Double strength Solarban 70 low-e glass, Intercept Spacer and argon gas fill |
| Viwinco Complementary Geometric Styles | January 1, 2016 | Geometric windows with grids only | none | 15/16" IG unit with Double strength Solarban 70 low-e glass, Intercept Spacer and argon gas fill |

P.O. Box 499 | 851 Hemlock Road
Morgantown, PA 19540-0499

610.286.8884 | F. 610.286.0600
Visit us at www.Viwinco.com



| STANDARD ZONE | | | | |
|---|-------------------------------------|--|-----------------|--|
| Product Line | Date Met. 2016 Energy Star Criteria | Style Details | Size Limitation | Glass Package Details of product supplied and shipped as of date listed: |
| NEW CONSTRUCTION | | | | |
| Builders Choice | January 1, 2016 | Double-hung and Single-hung with and without grids | 48" x 80" max | ¾" IG unit with single strength Solarban 70 low-e glass, Intercept ULTRA spacer and argon gas fill |
| Viwinco S-Series New Construction Windows | January 1, 2016 | Double-hung styles up to with and without grids | 48" x 72" max | 15/16" IG unit with double strength Solarban 70 low-e glass, Intercept ULTRA spacer and argon gas fill |
| | January 1, 2016 | Single-hung styles with and without grids | 48" x 72" max | 15/16" IG unit with double strength Solarban 70 low-e glass, Intercept ULTRA spacer and argon gas fill |
| | January 1, 2016 | Casement, Awning, Picture with and without grids | none | 15/16" IG unit with double strength Solarban 70 low-e glass, Intercept ULTRA spacer and argon gas fill |
| | January 1, 2016 | Double-hung styles up to with and without grids | 48" x 72" max | ¾" IG unit with single strength Solarban 70 low-e glass, Intercept Spacer and argon gas fill |
| | January 1, 2016 | Single-hung styles with and without grids | 48" x 72" max | ¾" IG unit with double strength Solarban 70 low-e glass, Intercept ULTRA spacer and argon gas fill |
| | January 1, 2016 | Casement, Awning, *Picture with and without grids | none | 15/16" IG unit with double strength Solarban 70 low-e glass, Intercept Spacer and argon gas fill <i>*Non-grid picture windows made with triple strength glass as of September 9, 2009</i> |
| Viwinco S-Series New Construction Geometric Styles | January 1, 2016 | Geometric windows with grids only | none | 15/16" IG unit with Double strength Solarban 70 low-e glass, Super spacer and argon gas fill |
| OceanView® New Construction Windows | January 1, 2016 | Double-hung and single-hung with and without grids | 48" x 72" max | 15/16" IG unit with laminated double strength Solarban 70 low-e glass, Intercept ULTRA spacer and argon gas fill |
| | January 1, 2016 | Casement, Awning, Picture with and without grids | none | 15/16" IG unit with laminated double strength Solarban 70 low-e glass, Intercept ULTRA spacer and argon gas fill |
| | January 1, 2016 | Double-hung and single-hung with and without grid | 48" x 72" max | 15/16" IG unit with laminated double strength Solarban 70 low-e glass, Intercept Spacer and argon gas fill |
| | January 1, 2016 | Casement, Awning, Picture with and without grids | none | 15/16" IG unit with laminated double strength Solarban 70 low-e glass, Intercept Spacer and argon gas fill |
| OceanView® New Construction Geometric Styles | January 1, 2016 | Geometric windows with grids only | none | 15/16" IG unit with laminated double strength Solarban 70 low-e glass, Super spacer and argon gas fill |

Taxpayers are not required to attach the Manufacturer's Certification Statement to their tax returns per the IRS but should retain this Certification as part of their tax records.

Viwinco, Inc. is not a legal nor a tax authority. Consult your tax advisor and review IRS guidelines prior to purchasing any Viwinco window product. Viwinco, Inc. wholly disclaims any responsibility for determining whether a purchaser will receive the energy tax credit. **Visit the IRS website for details about the 2016 Energy Tax Credit.**

P.O. Box 499 | 851 Hemlock Road | **610.286.8884** | F. 610.286.0600
Morgantown, PA 19540-0499 | [Visit us at www.Viwinco.com](http://www.Viwinco.com)

Impress the Weather



NORTHERN ZONE

| Product Line | Date Met. 2016 Energy Star Criteria | Style Details | Size Limitation | Glass Package Details of product supplied and shipped as of date listed: |
|---|-------------------------------------|---|-----------------|---|
| REPLACEMENT | | | | |
| Edgemont® | January 1, 2016 | Double-hung all styles | 36" x 72" max | ¾" IG unit with single strength ClimaGuard 72/57 low-e glass, Intercept ULTRA spacer and argon gas fill |
| | January 1, 2016 | Double-hung all styles | 48" x 72" max | ¾" IG unit with single strength ClimaGuard 72/57 low-e glass, Intercept ULTRA spacer and argon gas fill and composite reinforcement |
| | January 1, 2016 | Slider all styles | none | ¾" IG unit with single strength ClimaGuard 72/57 low-e glass, Intercept ULTRA spacer and argon gas fill (3 Litesliders are made with double strength glass) |
| | January 1, 2016 | Picture with grids only | none | ¾" IG unit with double strength ClimaGuard 72/57 low-e glass, Intercept ULTRA spacer and argon gas fill |
| Cambridge™ | January 1, 2016 | Double-hung & Single-hung with and without grids | 48" x 72" max | 15/16" IG unit with double strength ClimaGuard 72/57 low-e glass, Intercept ULTRA spacer and argon gas fill |
| | January 1, 2016 | Double-hung & Single-hung with and without grids | 48" x 72" max | ¾" IG unit with single strength ClimaGuard 72/57 low-e glass, Intercept spacer and argon gas fill |
| | January 1, 2016 | Slider styles all styles | none | 15/16" IG unit with Double strength ClimaGuard 72/57 low-e glass, Intercept ULTRA spacer and argon gas fill |
| | January 1, 2016 | *Picture all styles | none | 15/16" IG unit with Double strength ClimaGuard 72/57 low-e glass, Intercept ULTRA spacer and argon gas fill <i>*Non-grid picture windows made with triple strength glass as of September 9, 2009</i> |
| OceanView® | January 1, 2016 | Double-hung & single-hung with and without grids | 48" x 72" max | 15/16" IG unit with laminated double strength ClimaGuard 72/57 low-e glass, Intercept ULTRA spacer and argon gas fill |
| | January 1, 2016 | Casement, Awning, *Picture with and without grids | none | 15/16" IG unit with laminated double strength ClimaGuard 72/57 low-e glass, Intercept ULTRA spacer and argon gas fill <i>*Non-grid picture windows made with triple strength glass as of September 9, 2009</i> |
| | January 1, 2016 | Double-hung and single-hung with and without grid | 48" x 72" max | 15/16" IG unit with laminated double strength ClimaGuard 72/57 low-e glass, Intercept Spacer and argon gas fill |
| | January 1, 2016 | Casement, Awning, *Picture with and without grids | none | 15/16" IG unit with laminated double strength ClimaGuard 72/57 low-e glass, Intercept Spacer and argon gas fill <i>*Non-grid picture windows made with triple strength glass as of September 9, 2009</i> |
| | January 1, 2016 | Slider all styles | none | 15/16" IG unit with laminated double strength ClimaGuard 72/57 low-e glass, Intercept Spacer and argon gas fill |
| OceanView® Geometric Styles | January 1, 2016 | Geometric windows with grids only | none | 15/16" IG unit with laminated double strength ClimaGuard 72/57 low-e glass, Super spacer and argon gas fill |
| Viwinco Complementary Styles | January 1, 2016 | Casement & Awning | none | 15/16" IG unit with Double strength ClimaGuard 72/57 low-e glass, Intercept ULTRA spacer and argon gas fill |
| | January 1, 2016 | Casement & Awning | none | 15/16" IG unit with Double strength ClimaGuard 72/57 low-e glass, Intercept Spacer and argon gas fill |
| Viwinco Complementary Geometric Styles | January 1, 2016 | Geometric windows with grids only | none | 15/16" IG unit with Double strength ClimaGuard 72/57 low-e glass, Intercept Spacer and argon gas fill |

P.O. Box 499 | 851 Hemlock Road
Morgantown, PA 19540-0499

610.286.8884 | F. 610.286.0600

Visit us at www.Viwinco.com

Impress the Weather



| NORTHERN ZONE | | | | |
|---|-------------------------------------|--|-----------------|---|
| Product Line | Date Met. 2016 Energy Star Criteria | Style Details | Size Limitation | Glass Package Details of product supplied and shipped as of date listed: |
| NEW CONSTRUCTION | | | | |
| Builders Choice | January 1, 2016 | Double-hung and Single-hung with and without grids | 48" x 80" max | ¾" IG unit with single strength ClimaGuard 72/57 low-e glass, Intercept ULTRA spacer and argon gas fill |
| Viwinco S-Series New Construction Windows | January 1, 2016 | Double-hung styles up to with and without grids | 48" x 72" max | 15/16" IG unit with double strength ClimaGuard 72/57 low-e glass, Intercept ULTRA spacer and argon gas fill |
| | January 1, 2016 | Single-hung styles with and without grids | 48" x 72" max | 15/16" IG unit with double strength ClimaGuard 72/57 low-e glass, Intercept ULTRA spacer and argon gas fill |
| | January 1, 2016 | Casement, Awning, Picture with and without grids | none | 15/16" IG unit with double strength ClimaGuard 72/57 low-e glass, Intercept ULTRA spacer and argon gas fill |
| | January 1, 2016 | Double-hung styles up to with and without grids | 48" x 72" max | ¾" IG unit with single strength ClimaGuard 72/57 low-e glass, Intercept Spacer and argon gas fill |
| | January 1, 2016 | Single-hung styles with and without grids | 48" x 72" max | ¾" IG unit with double strength ClimaGuard 72/57 low-e glass, Intercept ULTRA spacer and argon gas fill |
| | January 1, 2016 | Casement, Awning, *Picture with and without grids | none | 15/16" IG unit with double strength ClimaGuard 72/57 low-e glass, Intercept Spacer and argon gas fill <i>*Non-grid picture windows made with triple strength glass as of September 9, 2009</i> |
| Viwinco S-Series New Construction Geometric Styles | January 1, 2016 | Geometric windows with grids only | none | 15/16" IG unit with Double strength ClimaGuard 72/57 low-e glass, Super spacer and argon gas fill |
| OceanView® New Construction Windows | January 1, 2016 | Double-hung and single-hung with and without grids | 48" x 72" max | 15/16" IG unit with laminated double strength ClimaGuard 72/57 low-e glass, Intercept ULTRA spacer and argon gas fill |
| | January 1, 2016 | Casement, Awning, Picture with and without grids | none | 15/16" IG unit with laminated double strength ClimaGuard 72/57 low-e glass, Intercept ULTRA spacer and argon gas fill |
| | January 1, 2016 | Double-hung and single-hung with and without grid | 48" x 72" max | 15/16" IG unit with laminated double strength ClimaGuard 72/57 low-e glass, Intercept Spacer and argon gas fill |
| | January 1, 2016 | Casement, Awning, Picture with and without grids | none | 15/16" IG unit with laminated double strength ClimaGuard 72/57 low-e glass, Intercept Spacer and argon gas fill |
| OceanView® New Construction Geometric Styles | January 1, 2016 | Geometric windows with grids only | none | 15/16" IG unit with laminated double strength ClimaGuard 72/57 low-e glass, Super spacer and argon gas fill |

Taxpayers are not required to attach the Manufacturer's Certification Statement to their tax returns per the IRS but should retain this Certification as part of their tax records.

Viwinco, Inc. is not a legal nor a tax authority. Consult your tax advisor and review IRS guidelines prior to purchasing any Viwinco window product. Viwinco, Inc. wholly disclaims any responsibility for determining whether a purchaser will receive the energy tax credit. **Visit the IRS website for details about the 2016 Energy Tax Credit.**

P.O. Box 499 | 851 Hemlock Road | **610.286.8884** | F. 610.286.0600
Morgantown, PA 19540-0499 | [Visit us at www.Viwinco.com](http://www.Viwinco.com)

Impress the Weather